

बिड दस्तावेज़ / Bid Document

बिड विवरण/Bid Details	
बिड बंद होने की तारीख/समय /Bid End Date/Time	08-12-2025 12:00:00
बिड खुलने की तारीख/समय /Bid Opening Date/Time	08-12-2025 12:30:00
बिड पेशकश वैधता (बंद होने की तारीख से)/Bid Offer Validity (From End Date)	30 (Days)
मंत्रालय/राज्य का नाम/Ministry/State Name	Maharashtra
विभाग का नाम/Department Name	Department Of Panchayati Raj
संगठन का नाम/Organisation Name	Pune District Panchayats
कार्यालय का नाम/Office Name	Mundhaware 186252
कुल मात्रा/Total Quantity	9
वस्तु श्रेणी /Item Category	Shoulder Builder / Arm Wheel - Outdoor Gym Equipment (Q3) , Leg Press - Outdoor Gym Equipments (Q3) , Twister - Outdoor Gym Equipment (Q3) , Chest Press - Outdoor Gym Equipments (Q3) , Surf Board - Outdoor Gym Equipment (Q3) , Air Walker / Stroller - Outdoor Gym Equipment (Q3) , Parallel Bar - Outdoor Gym Equipment (Q3)
उन्हीं/समान सेवा के लिए अपेक्षित विगत अनुभव के वर्ष/Years of Past Experience Required for same/similar service	1 Year (s)
एमएसएमई के लिए अनुभव के वर्षों और टर्नओवर से छूट प्रदान की गई है/MSE Exemption for Years of Experience and Turnover	No
स्टार्टअप के लिए अनुभव के वर्षों और टर्नओवर से छूट प्रदान की गई है /Startup Exemption for Years of Experience and Turnover	No
विक्रेता से मांगे गए दस्तावेज़/Document required from seller	Experience Criteria,Past Performance,Bidder Turnover,Certificate (Requested in ATC),Additional Doc 1 (Requested in ATC),Compliance of BoQ specification and supporting document *In case any bidder is seeking exemption from Experience / Turnover Criteria, the supporting documents to prove his eligibility for exemption must be uploaded for evaluation by the buyer
क्या आप निविदाकारों द्वारा अपलोड किए गए दस्तावेज़ों को निविदा में भाग लेने वाले सभी निविदाकारों को दिखाना चाहते हैं? संदर्भ मेनू है/Do you want to show documents uploaded by bidders to all bidders participated in bid?	No

बिड विवरण/Bid Details	
बिड लगाने की समय सीमा स्वतः नहीं बढ़ाने के लिए आवश्यक बिड की संख्या। / Minimum number of bids required to disable automatic bid extension	1
दिनों की संख्या, जिनके लिए बिड लगाने की समय-सीमा बढ़ाई जाएगी। / Number of days for which Bid would be auto-extended	3
ऑटो एक्सटेंशन अधिकतम कितनी बार किया जाना है। / Number of Auto Extension count	1
विगत प्रदर्शन / Past Performance	10 %
बिड से रिवर्स नीलामी सक्रिय किया/Bid to RA enabled	No
बिड का प्रकार/ Type of Bid	Two Packet Bid
प्राथमिक उत्पाद श्रेणी/ Primary product category	Shoulder Builder / Arm Wheel - Outdoor Gym Equipment
तकनीकी मूल्यांकन के दौरान तकनीकी स्पष्टीकरण हेतु अनुमत समय / Time allowed for Technical Clarifications during technical evaluation	2 Days
निरीक्षण आवश्यक (सूचीबद्ध निरीक्षण प्राधिकरण /जेम के साथ पूर्व पंजीकृत एजेंसियों द्वारा)/ Inspection Required (By Empanelled Inspection Authority / Agencies pre-registered with GeM)	No
Payment Timelines	Payments shall be made to the Seller within 45 days of issue of consignee receipt-cum-acceptance certificate (CRAC) and on-line submission of bills (This is in supersession of 10 days time as provided in clause 12 of GeM GTC)
मूल्यांकन पद्धति/ Evaluation Method	Total value wise evaluation
मध्यस्थता खंड/ Arbitration Clause	No
सुलह खंड/ Mediation Clause	No

ईएमडी विवरण/EMD Detail

आवश्यकता/Required	No
-------------------	----

ईपीबीजी विवरण /ePBG Detail

आवश्यकता/Required	No
-------------------	----

बोली विभाजन लागू नहीं किया गया/ Bid splitting not applied.

एमएसई खरीद वरीयता/MSE Purchase Preference

एमएसई खरीद वरीयता/MSE Purchase Preference	No
---	----

एमआईआई खरीद वरीयता/MII Purchase Preference

एमआईआई खरीद वरीयता/MII Purchase Preference	No
--	----

1. Experience Criteria: In respect of the filter applied for experience criteria, the Bidder or its OEM of the product offered in the bid {themselves or through reseller(s)} should have regularly, manufactured and supplied same or similar Category Products to any Central / State Govt Organization / PSU for number of Financial years as indicated above in the bid document before the bid opening date. Copies of relevant contracts and delivery acceptance certificates like CRAC to be submitted along with bid in support of having supplied some quantity during each of the Financial year. In case of bunch bids, the category of primary product having highest value should meet this criterion.

2. Past Performance: The Bidder or its OEM {themselves or through re-seller(s)} should have supplied same or similar Category Products for 10% of bid quantity, in at least one of the last three Financial years before the bid opening date to any Central / State Govt Organization / PSU. Copies of relevant contracts (proving supply of cumulative order quantity in any one financial year) to be submitted along with bid in support of quantity supplied in the relevant Financial year. In case of bunch bids, the category related to primary product having highest bid value should meet this criterion.

Shoulder Builder / Arm Wheel - Outdoor Gym Equipment (1 pieces)

तकनीकी विशिष्टियाँ /Technical Specifications

* जेम कैटेगरी विशिष्टि के अनुसार / As per GeM Category Specification

विवरण/Specification	विशिष्टि का नाम /Specification Name	बिड के लिए आवश्यक अनुमत मूल्य /Bid Requirement (Allowed Values)
TYPE	Type	Two Wheel, Three Wheel
MATERIAL	Governing Specification for GI Pipes	BIS specification No IS 1239 (Part 1)- 2004, latest, BIS specification No IS 1161:2014, latest
	All the GI Pipes are ISI marked	Yes, No
	Main Central Pipe construction	80mm Nominal Bore G.I. Pipe, 100mm Nominal Bore G.I. Pipe, 125 mm Nominal Bore G.I. Pipe, 150mm Nominal Bore G.I. Pipe
	Main Central Pipe, Class as per IS 1239	Medium, Heavy, Not applicable for pipe as per IS 1161
	Ring (Wheel)	25mm Nominal Bore G.I. Pipe, 32mm Nominal Bore G.I. Pipe, 40mm Nominal Bore G.I. Pipe
	Ring (Wheel) Pipe, Class as per IS 1239	Medium, Heavy, Not applicable for pipe as per IS 1161
	Pipe of Spokes of Wheel	15mm Nominal bore G.I. pipe, 20mm Nominal bore G.I. pipe
	Pipe of Spoke of Wheel , Class as per IS 1239	Medium, Heavy, Not applicable for pipe as per IS 1161

विवरण/Specification	विशिष्टि का नाम /Specification Name	बिड के लिए आवश्यक अनुमत मूल्य /Bid Requirement (Allowed Values)
	Connector Pipe (between Main Central Pipe and Wheel)	32 mm Nominal bore G.I. pipe, 40 mm Nominal bore G.I. pipe, 50 mm Nominal bore G.I. pipe
	Connector Pipe, Class as per IS 1239	Medium, Heavy, Not applicable for pipe as per IS 1161
	MS Foundation Plate Thickness	10, 12 (millimeter)
	Foundation Pipes with anchoring	750mm deep GI Pipe, supported with M.S. Angle 25 X 25 X 4mm, 500mm deep GI Pipe, supported with M.S. Angle 25 X 25 X 4mm
	Nominal Bore of Foundation Pipe	80mm, 100mm, 125mm, 150mm
	Foundation Pipe, Class as per IS 1239	Medium, Heavy, Not applicable for pipe as per IS 1161
	Bearings	Ball Bearing, Tapered Roller Bearing
OTHER REQUIREMENTS	Installation	Included, Not Included
CERTIFICATION	Certification (Safety and Quality Requirements)	As per European Standard EN 16630, No
WARRANTY	Warranty (years)	2, 3, 4, 5 (year)

परेषिती/रिपोर्टिंग अधिकारी तथा मात्रा/Consignees/Reporting Officer and Quantity

क्र.सं./S.No.	परेषिती/रिपोर्टिंग अधिकारी /Consignee Reporting/Officer	पता/Address	मात्रा /Quantity	डिलीवरी के दिन/Delivery Days
1	Parmeshwar Vinayakrao Gomsale	410405,AT MUDHAWARE TQ MAVAL DIST PUNE	1	150

Leg Press - Outdoor Gym Equipments (1 pieces)

तकनीकी विशिष्टियाँ /Technical Specifications

* जेम केटेगरी विशिष्टि के अनुसार / As per GeM Category Specification

विवरण/Specification	विशिष्टि का नाम /Specification Name	बिड के लिए आवश्यक अनुमत मूल्य /Bid Requirement (Allowed Values)
TYPE	Type	Leg Press Single, Leg Press Double
CAPACITY	Maximum User Weight (Kg)	100, 110, 120 (kilogram)

विवरण/Specification	विशिष्टि का नाम /Specification Name	बिड के लिए आवश्यक अनुमत मूल्य /Bid Requirement (Allowed Values)
MATERIAL	Governing Specification for GI Pipes	BIS specification No IS 1239 (Part 1)- 2004, latest, BIS specification No IS 1161:2014, latest
	All the GI Pipes are ISI marked	Yes, No
	Main Central Pipe	80mm Nominal Bore G.I. Pipe, 100mm Nominal Bore G.I. Pipe, 125 mm Nominal Bore G.I. Pipe, 150mm Nominal Bore G.I. Pipe
	Main Central Pipe, Class as per IS 1239	Medium, Heavy, Not applicable for pipe as per IS 1161
	Moving Frame Pipe	32mm Nominal bore G.I. pipe, 40mm Nominal bore G.I. pipe
	Moving Frame Pipe, Class as per IS 1239	Medium, Heavy, Not applicable for pipe as per IS 1161
	Foot Rest Frame/ Foot Rest Hinging Pipe	25mm Nominal Bore G.I. Pipe, 32mm Nominal Bore G.I. Pipe
	Foot Rest Frame Pipe, Class as per IS 1239	Medium, Heavy, Not applicable for M.S. Plates
	Connecting Links	25mm Nominal Bore G.I. Pipe, 32mm Nominal Bore G.I. Pipe, 40mm Nominal Bore G.I. Pipe, 10mm thick MS plates, 12mm thick MS plates
	Connecting Links Pipe, Class as per IS 1239	Medium, Heavy, Not applicable for M.S. Plates and Pipes as per IS 1161
	MS Foundation Plate Thickness	10, 12 (millimeter)
	Foundation Pipes with anchoring	750mm deep GI Pipe, supported with M.S. Angle 25 X 25 X 4mm, 500mm deep GI Pipe, supported with M.S. Angle 25 X 25 X 4mm
	Nominal Bore of Foundation Pipe	80mm, 100mm, 125mm, 150mm
	Foundation Pipe, Class as per IS 1239	Medium, Heavy, Not applicable for pipe as per IS 1161
	Bearings	Ball Bearing, Tapered Roller Bearing
	Seat and Back Rest	2mm Thick G.I. Seat with uniform bending radius to avoid sharp edges, 3mm thick, HDPE with uniform bending radius to avoid sharp edges, 6mm thick, Fibre Reinforced plastic with uniform bending radius to avoid sharp edges, 2.5mm thick, M.S. Perforated with uniform bending radius to avoid sharp edges, 3mm thick, LLDPE with uniform bending radius to avoid sharp edges
OTHER REQUIREMENTS	Installation	Included, Not Included
CERTIFICATION	Certification (Safety and Quality Requirements)	As per European Standard EN 16630, No
WARRANTY	Warranty (years)	2, 3, 4, 5 (year)

परेषिती/रिपोर्टिंग अधिकारी तथा मात्रा/Consignees/Reporting Officer and Quantity

क्र.सं./S.No.	परेषिती/रिपोर्टिंग अधिकारी /Consignee Reporting/Officer	पता/Address	मात्रा /Quantity	डिलीवरी के दिन/Delivery Days
1	Parmeshwar Vinayakrao Gomsale	410405,AT MUDHAWARE TQ MAVAL DIST PUNE	1	150

Twister - Outdoor Gym Equipment (1 pieces)

तकनीकी विशिष्टियाँ /Technical Specifications

* जेम कैटेगरी विशिष्टि के अनुसार / As per GeM Category Specification

विवरण/Specification	विशिष्टि का नाम /Specification Name	बिड के लिए आवश्यक अनुमत मूल्य /Bid Requirement (Allowed Values)
TYPE	Type	Double Twister (Both Standing), Double Twister (Both Sitting), Double Twister (One standing and one sitting), Triple Twister (Three standing), Triple Twister (Three Sitting), Tripple Twister (Two standing, one sitting), Tripple Twister (one standing, two sitting), Single Twister Standing, Single Twister Sitting
CAPACITY	Maximum User Weight (Kg)	100, 110, 120 (kilogram)
MATERIAL	Governing Specification for GI Pipes	BIS specification No IS 1239 (Part 1)- 2004, latest, BIS specification No IS 1161:2014, latest
	All the GI Pipes are ISI marked	Yes, No
	Main Central Pipe	80mm Nominal Bore G.I. Pipe, 100mm Nominal Bore G.I. Pipe, 125 mm Nominal Bore G.I. Pipe, 150mm Nominal Bore G.I. Pipe
	Main Frame Pipe, Class as per IS 1239	Medium, Heavy, Not applicable for pipe as per IS 1161

विवरण/Specification	विशिष्टि का नाम /Specification Name	बिड के लिए आवश्यक अनुमत मूल्य /Bid Requirement (Allowed Values)
	Main Central Pipe (As per Clause 3, of IS 1161) Nominal Bore & Wall Thickness	80 mm NB with 3.2 mm Thickness, 80 mm NB with 4 mm Thickness, 80 mm NB with 4.8 mm Thickness, 100 mm NB with 3.6 mm Thickness, 100 mm NB with 4.5 mm Thickness, 100 mm NB with 5.4 mm Thickness, 125 mm NB with 4.5 mm Thickness, 125mm NB with 4.8 mm Thickness, 125 mm NB with 5.4 mm Thickness, 150 mm NB,165.1 mm OD & 4.5 mm Thickness, 150 mm NB,165.1 mm OD & 4.8 mm Thickness, 150 mm NB,165.1 mm OD & 5.4 mm Thickness, 150 mm NB,165.1 mm OD & 5.9 mm Thickness, 150 mm NB,165.1 mm OD & 6.3 mm Thickness, 150 mm NB,165.1 mm OD & 8 mm Thickness, 150 mm NB,168.3 mm OD & 4.5 mm Thickness, 150 mm NB,168.3 mm OD & 4.8 mm Thickness, 150 mm NB,168.3 mm OD & 5.4 mm Thickness, 150 mm NB,168.3 mm OD & 6.3 mm Thickness, 150 mm NB,168.3 mm OD & 8 mm Thickness, 150 mm NB,168.3 mm OD & 10 mm Thickness, Not Applicable
	Grade Material as per table 2 of IS 1161	YSt 210, YSt 240, YSt 310, YSt 355, Not Applicable
	Standing/ Sitting Twister Frame Pipe	25 mm Nominal Bore G.I. Pipe, 32 mm Nominal Bore G.I. Pipe, 40 mm Nominal Bore G.I. Pipe, 50 mm Nominal Bore G.I. Pipe
	Standing/ Sitting Twister Frame Pipe, Class as per IS 1239	Medium, Heavy, Not applicable for pipe as per IS 1161
	Standing/ Sitting Twister Frame Pipe (As per Clause 3, of IS 1161) Nominal Bore & Wall Thickness	32 mm NB with 2.6 mm Thickness, 32 mm NB with 3.2 mm Thickness, 32 mm NB with 4 mm Thickness, 40 mm NB with 2.9 mm Thickness, 40 mm NB with 3.2 mm Thickness, 40 mm NB with 4 mm Thickness, 50 mm NB with 2.9 mm Thickness, 50 mm NB with 3.6 mm Thickness, 50 mm NB with 4.5 mm Thickness, 25 mm NB with 2.6 mm Thickness, 25 mm NB with 3.2 mm Thickness, 25 mm NB with 4 mm Thickness, Not Applicable
	Grade Material as per table 2 IS 1161	YSt 210, YSt 240, YSt 310, YSt 355, Not Applicable
	Rotating Disk Support Pipe at Bottom Pipe	80 mm Nominal Bore G.I. Pipe, 100 mm Nominal Bore G.I. Pipe, 125 mm Nominal Bore G.I. Pipe, 150 mm Nominal Bore G.I. Pipe
	Rotating Disk Support Pipe, Class as per IS 1239	Medium, Heavy, Not applicable for M.S. Plates and Pipes as per IS 1161

विवरण/Specification	विशिष्टि का नाम /Specification Name	बिड के लिए आवश्यक अनुमत मूल्य /Bid Requirement (Allowed Values)
	Rotating Disk Support Pipe (as per IS 1161) as per Clause 3, Nominal Bore & Wall Thickness	80 mm NB with 3.2 mm Thickness, 80 mm NB with 4 mm Thickness, 80 mm NB with 4.8 mm Thickness, 100 mm NB with 3.6 mm Thickness, 100 mm NB with 4.5 mm Thickness, 100 mm NB with 5.4 mm Thickness, 125 mm NB with 4.5 mm Thickness, 125mm NB with 4.8 mm Thickness, 125 mm NB with 5.4 mm Thickness, 150 mm NB,165.1 mm OD & 4.5 mm Thickness, 150 mm NB,165.1 mm OD & 4.8 mm Thickness, 150 mm NB,165.1 mm OD & 5.4 mm Thickness, 150 mm NB,165.1 mm OD & 5.9 mm Thickness, 150 mm NB,165.1 mm OD & 6.3 mm Thickness, 150 mm NB,165.1 mm OD & 8 mm Thickness, 150 mm NB,168.3 mm OD & 4.5 mm Thickness, 150 mm NB,168.3 mm OD & 4.8 mm Thickness, 150 mm NB,168.3 mm OD & 5.4 mm Thickness, 150 mm NB,168.3 mm OD & 6.3 mm Thickness, 150 mm NB,168.3 mm OD & 8 mm Thickness, 150 mm NB,168.3 mm OD & 10mm Thickness, Not Applicable
	Grade Material (as per table 2 of IS 1161)	YSt 210, YSt 240, YSt 310, YSt 355, Not Applicable
	Handle Frame Pipe	25mm Nominal bore G.I. pipe, 32mm Nominal bore G.I. pipe, 40 mm Nominal bore G.I. pipe
	Handle Frame Pipe, Class as per IS 1239	Medium, Heavy, Not applicable for pipe as per IS 1161
	Handle Frame Pipe (as per IS 1161) as per clause 3, Nominal Wall & Thickness	25 mm NB with 2.6 mm Thickness, 25 mm NB with 3.2 mm Thickness, 25 mm NB with 4 mm Thickness, 32 mm NB with 2.6 mm Thickness, 32 mm NB with 3.2 mm Thickness, 32 mm NB with 4 mm Thickness, 40 mm NB with 2.9 mm Thickness, 40 mm NB with 3.2 mm Thickness, 40 mm NB with 4 mm Thickness, Not Applicable
	Grade Material per table 2 of IS 1161	YSt 210, YSt 240, YSt 310, YSt 355, Not Applicable
	Foundation Pipes with anchoring	750mm deep GI Pipe, supported with M.S. Angle 25 X 25 X 4mm, 500mm deep GI Pipe, supported with M.S. Angle 25 X 25 X 4mm
	Nominal Bore of Foundation Pipe	80mm, 100mm, 125mm, 150mm
	Foundation Pipe, Class as per IS 1239	Medium, Heavy, Not applicable for pipe as per IS 1161

विवरण/Specification	विशिष्टि का नाम /Specification Name	बिड के लिए आवश्यक अनुमत मूल्य /Bid Requirement (Allowed Values)
	Foundation Pipe Pipe (as per IS 1161) as per clause 3, Nominal Wall & Thickness	80 mm NB with 3.2 mm Thickness, 80 mm NB with 4 mm Thickness, 80 mm NB with 4.8 mm Thickness, 100 mm NB with 3.6 mm Thickness, 100 mm NB with 4.5 mm Thickness, 100 mm NB with 5.4 mm Thickness, 125 mm NB with 4.5 mm Thickness, 125mm NB with 4.8 mm Thickness, 125 mm NB with 5.4 mm Thickness, 150 mm NB,165.1 mm OD & 4.5 mm Thickness, 150 mm NB,165.1 mm OD & 4.8 mm Thickness, 150 mm NB,165.1 mm OD & 5.4 mm Thickness, 150 mm NB,165.1 mm OD & 5.9 mm Thickness, 150 mm NB,165.1 mm OD & 6.3 mm Thickness, 150 mm NB,165.1 mm OD & 8 mm Thickness, 150 mm NB,168.3 mm OD & 4.5 mm Thickness, 150 mm NB,168.3 mm OD & 4.8 mm Thickness, 150 mm NB,168.3 mm OD & 5.4 mm Thickness, 150 mm NB,168.3 mm OD & 6.3 mm Thickness, 150 mm NB,168.3 mm OD & 8 mm Thickness, 150 mm NB,168.3 mm OD & 10 mm Thickness, Not Applicable
	Grade Material (as per table 2 of IS 1161)	YSt 210, YSt 240, YSt 310, YSt 355, Not Applicable
	M S Foundation Plate Thickness	10, 12 (millimeter)
	Bearings	Ball Bearing, Tapered Roller Bearing
	Foot Rest	Fibre Reinforced Plastic, Aluminum casting material, C.I., LDPE, HDPE, Nylon
OTHER REQUIREMENTS	Installation	Included, Not Included
CERTIFICATION	Certification (Safety and Quality Requirements)	As per European Standard EN 16630, No
WARRANTY	Warranty (years)	2, 3, 4, 5 (year)

प्रेषिती/रिपोर्टिंग अधिकारी तथा मात्रा/Consignees/Reporting Officer and Quantity

क्र.सं./S.No.	प्रेषिती/रिपोर्टिंग अधिकारी /Consignee Reporting/Officer	पता/Address	मात्रा /Quantity	डिलीवरी के दिन/Delivery Days
1	Parmeshwar Vinayakrao Gomsale	410405,AT MUDHAWARE TQ MAVAL DIST PUNE	1	150

Twister - Outdoor Gym Equipment (1 pieces)

तकनीकी विशिष्टियाँ /Technical Specifications

* जेम केटेगरी विशिष्टि के अनुसार / As per GeM Category Specification

विवरण/Specification	विशिष्टि का नाम /Specification Name	बिड के लिए आवश्यक अनुमत मूल्य /Bid Requirement (Allowed Values)
TYPE	Type	Double Twister (Both Standing), Double Twister (Both Sitting), Double Twister (One standing and one sitting), Triple Twister (Three standing), Triple Twister (Three Sitting), Tripple Twister (Two standing, one sitting), Tripple Twister (one standing, two sitting), Single Twister Standing, Single Twister Sitting
CAPACITY	Maximum User Weight (Kg)	100, 110, 120 (kilogram)
MATERIAL	Governing Specification for GI Pipes	BIS specification No IS 1239 (Part 1)- 2004, latest, BIS specification No IS 1161:2014, latest
	All the GI Pipes are ISI marked	Yes, No
	Main Central Pipe	80mm Nominal Bore G.I. Pipe, 100mm Nominal Bore G.I. Pipe, 125 mm Nominal Bore G.I. Pipe, 150mm Nominal Bore G.I. Pipe
	Main Frame Pipe, Class as per IS 1239	Medium, Heavy, Not applicable for pipe as per IS 1161
	Main Central Pipe (As per Clause 3, of IS 1161) Nominal Bore & Wall Thickness	80 mm NB with 3.2 mm Thickness, 80 mm NB with 4 mm Thickness, 80 mm NB with 4.8 mm Thickness, 100 mm NB with 3.6 mm Thickness, 100 mm NB with 4.5 mm Thickness, 100 mm NB with 5.4 mm Thickness, 125 mm NB with 4.5 mm Thickness, 125mm NB with 4.8 mm Thickness, 125 mm NB with 5.4 mm Thickness, 150 mm NB,165.1 mm OD & 4.5 mm Thickness, 150 mm NB,165.1 mm OD & 4.8 mm Thickness, 150 mm NB,165.1 mm OD & 5.4 mm Thickness, 150 mm NB,165.1 mm OD & 5.9 mm Thickness, 150 mm NB,165.1 mm OD & 6.3 mm Thickness, 150 mm NB,165.1 mm OD & 8 mm Thickness, 150 mm NB,168.3 mm OD & 4.5 mm Thickness, 150 mm NB,168.3 mm OD & 4.8 mm Thickness, 150 mm NB,168.3 mm OD & 5.4 mm Thickness, 150 mm NB,168.3 mm OD & 6.3 mm Thickness, 150 mm NB,168.3 mm OD & 8 mm Thickness, 150 mm NB,168.3 mm OD & 10 mm Thickness, Not Applicable
	Grade Material as per table 2 of IS 1161	YSt 210, YSt 240, YSt 310, YSt 355, Not Applicable
	Standing/ Sitting Twister Frame Pipe	25 mm Nominal Bore G.I. Pipe, 32 mm Nominal Bore G.I. Pipe, 40 mm Nominal Bore G.I. Pipe, 50 mm Nominal Bore G.I. Pipe
	Standing/ Sitting Twister Frame Pipe, Class as per IS 1239	Medium, Heavy, Not applicable for pipe as per IS 1161

विवरण/Specification	विशिष्टि का नाम /Specification Name	बिड के लिए आवश्यक अनुमत मूल्य /Bid Requirement (Allowed Values)
	Standing/ Sitting Twister Frame Pipe (As per Clause 3, of IS 1161) Nominal Bore & Wall Thickness	32 mm NB with 2.6 mm Thickness, 32 mm NB with 3.2 mm Thickness, 32 mm NB with 4 mm Thickness, 40 mm NB with 2.9 mm Thickness, 40 mm NB with 3.2 mm Thickness, 40 mm NB with 4 mm Thickness, 50 mm NB with 2.9 mm Thickness, 50 mm NB with 3.6 mm Thickness, 50 mm NB with 4.5 mm Thickness, 25 mm NB with 2.6 mm Thickness, 25 mm NB with 3.2 mm Thickness, 25 mm NB with 4 mm Thickness, Not Applicable
	Grade Material as per table 2 IS 1161	YSt 210, YSt 240, YSt 310, YSt 355, Not Applicable
	Rotating Disk Support Pipe at Bottom Pipe	80 mm Nominal Bore G.I. Pipe, 100 mm Nominal Bore G.I. Pipe, 125 mm Nominal Bore G.I. Pipe, 150 mm Nominal Bore G.I. Pipe
	Rotating Disk Support Pipe, Class as per IS 1239	Medium, Heavy, Not applicable for M.S. Plates and Pipes as per IS 1161
	Rotating Disk Support Pipe (as per IS 1161) as per Clause 3, Nominal Bore & Wall Thickness	80 mm NB with 3.2 mm Thickness, 80 mm NB with 4 mm Thickness, 80 mm NB with 4.8 mm Thickness, 100 mm NB with 3.6 mm Thickness, 100 mm NB with 4.5 mm Thickness, 100 mm NB with 5.4 mm Thickness, 125 mm NB with 4.5 mm Thickness, 125mm NB with 4.8 mm Thickness, 125 mm NB with 5.4 mm Thickness, 150 mm NB,165.1 mm OD & 4.5 mm Thickness, 150 mm NB,165.1 mm OD & 4.8 mm Thickness, 150 mm NB,165.1 mm OD & 5.4 mm Thickness, 150 mm NB,165.1 mm OD & 5.9 mm Thickness, 150 mm NB,165.1 mm OD & 6.3 mm Thickness, 150 mm NB,165.1 mm OD & 8 mm Thickness, 150 mm NB,168.3 mm OD & 4.5 mm Thickness, 150 mm NB,168.3 mm OD & 4.8 mm Thickness, 150 mm NB,168.3 mm OD & 5.4 mm Thickness, 150 mm NB,168.3 mm OD & 6.3 mm Thickness, 150 mm NB,168.3 mm OD & 8 mm Thickness, 150 mm NB,168.3 mm OD & 10mm Thickness, Not Applicable
	Grade Material (as per table 2 of IS 1161)	YSt 210, YSt 240, YSt 310, YSt 355, Not Applicable
	Handle Frame Pipe	25mm Nominal bore G.I. pipe, 32mm Nominal bore G.I. pipe, 40 mm Nominal bore G.I. pipe
	Handle Frame Pipe, Class as per IS 1239	Medium, Heavy, Not applicable for pipe as per IS 1161
	Handle Frame Pipe (as per IS 1161) as per clause 3, Nominal Wall & Thickness	25 mm NB with 2.6 mm Thickness, 25 mm NB with 3.2 mm Thickness, 25 mm NB with 4 mm Thickness, 32 mm NB with 2.6 mm Thickness, 32 mm NB with 3.2 mm Thickness, 32 mm NB with 4 mm Thickness, 40 mm NB with 2.9 mm Thickness, 40 mm NB with 3.2 mm Thickness, 40 mm NB with 4 mm Thickness, Not Applicable
	Grade Material per table 2 of IS 1161	YSt 210, YSt 240, YSt 310, YSt 355, Not Applicable

विवरण/Specification	विशिष्टि का नाम /Specification Name	बिड के लिए आवश्यक अनुमत मूल्य /Bid Requirement (Allowed Values)
	Foundation Pipes with anchoring	750mm deep GI Pipe, supported with M.S. Angle 25 X 25 X 4mm, 500mm deep GI Pipe, supported with M.S. Angle 25 X 25 X 4mm
	Nominal Bore of Foundation Pipe	80mm, 100mm, 125mm, 150mm
	Foundation Pipe, Class as per IS 1239	Medium, Heavy, Not applicable for pipe as per IS 1161
	Foundation Pipe (as per IS 1161) as per clause 3, Nominal Wall & Thickness	80 mm NB with 3.2 mm Thickness, 80 mm NB with 4 mm Thickness, 80 mm NB with 4.8 mm Thickness, 100 mm NB with 3.6 mm Thickness, 100 mm NB with 4.5 mm Thickness, 100 mm NB with 5.4 mm Thickness, 125 mm NB with 4.5 mm Thickness, 125mm NB with 4.8 mm Thickness, 125 mm NB with 5.4 mm Thickness, 150 mm NB,165.1 mm OD & 4.5 mm Thickness, 150 mm NB,165.1 mm OD & 4.8 mm Thickness, 150 mm NB,165.1 mm OD & 5.4 mm Thickness, 150 mm NB,165.1 mm OD & 5.9 mm Thickness, 150 mm NB,165.1 mm OD & 6.3 mm Thickness, 150 mm NB,165.1 mm OD & 8 mm Thickness, 150 mm NB,168.3 mm OD & 4.5 mm Thickness, 150 mm NB,168.3 mm OD & 4.8 mm Thickness, 150 mm NB,168.3 mm OD & 5.4 mm Thickness, 150 mm NB,168.3 mm OD & 6.3 mm Thickness, 150 mm NB,168.3 mm OD & 8 mm Thickness, 150 mm NB,168.3 mm OD & 10 mm Thickness, Not Applicable
	Grade Material (as per table 2 of IS 1161)	YSt 210, YSt 240, YSt 310, YSt 355, Not Applicable
	M S Foundation Plate Thickness	10, 12 (millimeter)
	Bearings	Ball Bearing, Tapered Roller Bearing
	Foot Rest	Fibre Reinforced Plastic, Aluminum casting material, C.I., LDPE, HDPE, Nylon
OTHER REQUIREMENTS	Installation	Included, Not Included
CERTIFICATION	Certfication (Safety and Quality Requirements)	As per European Standard EN 16630, No
WARRANTY	Warranty (years)	2, 3, 4, 5 (year)

परेषिती/रिपोर्टिंग अधिकारी तथा मात्रा/Consignees/Reporting Officer and Quantity

क्र.सं./S.No.	प्रेषिती/रिपोर्टिंग अधिकारी /Consignee Reporting/Officer	पता/Address	मात्रा /Quantity	डिलीवरी के दिन/Delivery Days
1	Parmeshwar Vinayakrao Gomsale	410405,AT MUDHAWARE TQ MAVAL DIST PUNE	1	150

Chest Press - Outdoor Gym Equipments (1 pieces)

तकनीकी विशिष्टियाँ /Technical Specifications

[* जेम केटेगरी विशिष्टि के अनुसार / As per GeM Category Specification](#)

विवरण/Specification	विशिष्टि का नाम /Specification Name	बिड के लिए आवश्यक अनुमत मूल्य /Bid Requirement (Allowed Values)
TYPE	Type	Chest Press Single, Chest Press Double
CAPACITY	Maximum User Weight (Kg)	100, 110, 120 (kilogram)
MATERIAL	Governing Specification for GI Pipes	BIS specification No IS 1239 (Part 1)- 2004, latest, BIS specification No IS 1161:2014, latest
	All the GI Pipes are ISI marked	Yes, No
	Main Central Pipe	80mm Nominal Bore G.I. Pipe, 100mm Nominal Bore G.I. Pipe, 125 mm Nominal Bore G.I. Pipe, 150mm Nominal Bore G.I. Pipe
	Main Central Pipe, Class as per IS 1239	Medium, Heavy, Not applicable for pipe as per IS 1161
	Handle Frame	32mm Nominal bore G.I. pipe, 40mm Nominal bore G.I. pipe
	Handle Frame Pipe, Class as per IS 1239	Medium, Heavy, Not applicable for pipe as per IS 1161
	Seat Frame	32mm Nominal Bore G.I. Pipe, 40mm Nominal Bore G.I. Pipe
	Seat Frame Pipe, Class as per IS 1239	Medium, Heavy, Not applicable for pipe as per IS 1161
	Connecting Links	25mm Nominal Bore G.I. Pipe, 32mm Nominal Bore G.I. Pipe, 40mm Nominal Bore G.I. Pipe, 10mm thick MS plates, 12mm thick MS plates
	Connecting Links Pipe, Class as per IS 1239	Medium, Heavy, Not applicable for M.S. Plates and Pipes as per IS 1161
	Foot Rest Pipe	25mm Nominal Bore G.I. Pipe, 32mm Nominal Bore G.I. Pipe
	Foot Rest Pipe, Class as per IS 1239	Medium, Heavy, Not applicable for pipe as per IS 1161
	MS Foundation Plate Thickness	10, 12 (millimeter)

विवरण/Specification	विशिष्टि का नाम /Specification Name	बिड के लिए आवश्यक अनुमत मूल्य /Bid Requirement (Allowed Values)
	Foundation Pipes with anchoring	750mm deep GI Pipe, supported with M.S. Angle 25 X 25 X 4mm, 500mm deep GI Pipe, supported with M.S. Angle 25 X 25 X 4mm
	Nominal Bore of Foundation Pipe	80mm, 100mm, 125mm, 150mm
	Foundation Pipe, Class as per IS 1239	Medium, Heavy, Not applicable for pipe as per IS 1161
	Seat and Back Rest	2mm Thick G.I. Seat with uniform bending radius to avoid sharp edges, 3mm thick, HDPE with uniform bending radius to avoid sharp edges, 6mm thick, Fibre Reinforced plastic with uniform bending radius to avoid sharp edges, 2.5mm thick, M.S. Perforated with uniform bending radius to avoid sharp edges, 3mm thick, LLDPE with uniform bending radius to avoid sharp edges
	Bearings	Ball Bearing, Tapered Roller Bearing
OTHER REQUIREMENTS	Installation	Included, Not Included
CERTIFICATION	Certification (Safety and Quality Requirements)	As per European Standard EN 16630, No
WARRANTY	Warranty (years)	2, 3, 4, 5 (year)

परेषिती/रिपोर्टिंग अधिकारी तथा मात्रा/Consignees/Reporting Officer and Quantity

क्र.सं./S.No.	परेषिती/रिपोर्टिंग अधिकारी /Consignee Reporting/Officer	पता/Address	मात्रा /Quantity	डिलीवरी के दिन/Delivery Days
1	Parmeshwar Vinayakrao Gomsale	410405,AT MUDHAWARE TQ MAVAL DIST PUNE	1	150

Surf Board - Outdoor Gym Equipment (1 pieces)

तकनीकी विशिष्टियाँ /Technical Specifications

* जेम कैटेगरी विशिष्टि के अनुसार / As per GeM Category Specification

विवरण/Specification	विशिष्टि का नाम /Specification Name	बिड के लिए आवश्यक अनुमत मूल्य /Bid Requirement (Allowed Values)
TYPE	Type	Single, Double
CAPACITY	Maximum User Weight (Kg)	100, 110, 120 (kilogram)

विवरण/Specification	विशिष्टि का नाम /Specification Name	बिड के लिए आवश्यक अनुमत मूल्य /Bid Requirement (Allowed Values)
MATERIAL	Governing Specification for GI Pipes	BIS specification No IS 1239 (Part 1)- 2004, latest, BIS specification No IS 1161:2014, latest
	All the GI Pipes are ISI marked	Yes, No
	Main Central Pipe	80mm Nominal Bore G.I. Pipe, 100mm Nominal Bore G.I. Pipe, 125 mm Nominal Bore G.I. Pipe, 150mm Nominal Bore G.I. Pipe
	Main Frame Pipe, Class as per IS 1239	Medium, Heavy, Not applicable for pipe as per IS 1161
	Main Central Pipe (As per Clause 3, of IS 1161) Nominal Bore & Wall Thickness	80 mm NB with 3.2 mm Thickness, 80 mm NB with 4 mm Thickness, 80 mm NB with 4.8 mm Thickness, 100 mm NB with 3.6 mm Thickness, 100 mm NB with 4.5 mm Thickness, 100 mm NB with 5.4 mm Thickness, 125 mm NB with 4.5 mm Thickness, 125mm NB with 4.8 mm Thickness, 125 mm NB with 5.4 mm Thickness, 150 mm NB,165.1 mm OD & 4.5 mm Thickness, 150 mm NB,165.1 mm OD & 4.8 mm Thickness, 150 mm NB,165.1 mm OD & 5.4 mm Thickness, 150 mm NB,165.1 mm OD & 5.9 mm Thickness, 150 mm NB,165.1 mm OD & 6.3 mm Thickness, 150 mm NB,165.1 mm OD & 8 mm Thickness, 150 mm NB,168.3 mm OD & 4.5 mm Thickness, 150 mm NB,168.3 mm OD & 4.8 mm Thickness, 150 mm NB,168.3 mm OD & 5.4 mm Thickness, 150 mm NB,168.3 mm OD & 6.3 mm Thickness, 150 mm NB,168.3 mm OD & 8 mm Thickness, 150 mm NB,168.3 mm OD & 10 mm Thickness, Not Applicable
	Grade Material as per table 2 of IS 1161	YSt 210, YSt 240, YSt 310, YSt 355, Not Applicable
	Movement (Paddle) Frame	32mm Nominal Bore G.I. Pipe, 40mm Nominal Bore G.I. Pipe, 50mm Nominal Bore G.I. Pipe
	Movement (Paddle) Frame Pipe, Class as per IS 1239	Medium, Heavy, Not applicable for pipe as per IS 1161
	Movement (Paddle) Frame Pipe (As per as per Clause 3, of IS 1161) , Nominal Bore & Wall Thickness	32 mm NB with 2.6 mm Thickness, 32 mm NB with 3.2 mm Thickness, 32 mm NB with 4 mm Thickness, 40 mm NB with 2.9 mm Thickness, 40 mm NB with 3.2 mm Thickness, 40 mm NB with 4 mm Thickness, 50 mm NB with 2.9 mm Thickness, 50 mm NB with 3.6 mm Thickness, 50 mm NB with 4.5 mm Thickness, Not Applicable
	Grade Material as per table 2 IS 1161	YSt 210, YSt 240, YSt 310, YSt 355, Not Applicable
	Connecting Links	25 mm Nominal Bore G.I. Pipe, 32 mm Nominal Bore G.I. Pipe, 40 mm Nominal Bore G.I. Pipe, 10 mm thick MS plates, 12 mm thick MS plates
	Connecting Links Pipe, Class as per IS 1239	Medium, Heavy, Not applicable for M.S. Plates and Pipes as per IS 1161

विवरण/Specification	विशिष्टि का नाम /Specification Name	बिड के लिए आवश्यक अनुमत मूल्य /Bid Requirement (Allowed Values)
	Connecting Link Pipe (As per Clause 3, of IS 1161) Nominal Wall & Thickness	25 mm NB with 2.6 mm Thickness, 25 mm NB with 3.2 mm Thickness, 25 mm NB with 4 mm Thickness, 32 mm NB with 2.6 mm Thickness, 32 mm NB with 3.2 mm Thickness, 32 mm NB with 4 mm Thickness, 40 mm NB with 2.9 mm Thickness, 40 mm NB with 3.2 mm Thickness, 40 mm NB with 4 mm Thickness, Not Applicable
	Grade Material (as per table 2 of IS 1161)	YSt 210, YSt 240, YSt 310, YSt 355, Not Applicable
	Handle Frame	25mm Nominal bore G.I. pipe, 32mm Nominal bore G.I. pipe
	Handle Frame Pipe, Class as per IS 1239	Medium, Heavy, Not applicable for pipe as per IS 1161
	Handle Frame Pipe (as per IS 1161) as per clause 3, Nominal Wall & Thickness	25 mm NB with 2.6 mm Thickness, 25 mm NB with 3.2 mm Thickness, 25 mm NB with 4 mm Thickness, 32 mm NB with 2.6 mm Thickness, 32 mm NB with 3.2 mm Thickness, 32 mm NB with 4 mm Thickness, Not Applicable
	Grade Material per table 2 of IS 1161	YSt 210, YSt 240, YSt 310, YSt 355, Not Applicable
	Foundation Pipes with anchoring	750mm deep GI Pipe, supported with M.S. Angle 25 X 25 X 4mm, 500mm deep GI Pipe, supported with M.S. Angle 25 X 25 X 4mm
	Nominal Bore of Foundation Pipe	80mm, 100mm, 125mm, 150mm
	Foundation Pipe, Class as per IS 1239	Medium, Heavy, Not applicable for pipe as per IS 1161
	Foundation Pipe Pipe (as per IS 1161) as per clause 3, Nominal Wall & Thickness	80 mm NB with 3.2 mm Thickness, 80 mm NB with 4 mm Thickness, 80 mm NB with 4.8 mm Thickness, 100 mm NB with 3.6 mm Thickness, 100 mm NB with 4.5 mm Thickness, 100 mm NB with 5.4 mm Thickness, 125 mm NB with 4.5 mm Thickness, 125mm NB with 4.8 mm Thickness, 125 mm NB with 5.4 mm Thickness, 150 mm NB,165.1 mm OD & 4.5 mm Thickness, 150 mm NB,165.1 mm OD & 4.8 mm Thickness, 150 mm NB,165.1 mm OD & 5.4 mm Thickness, 150 mm NB,165.1 mm OD & 5.9 mm Thickness, 150 mm NB,165.1 mm OD & 6.3 mm Thickness, 150 mm NB,165.1 mm OD & 8 mm Thickness, 150 mm NB,168.3 mm OD & 4.5 mm Thickness, 150 mm NB,168.3 mm OD & 4.8 mm Thickness, 150 mm NB,168.3 mm OD & 5.4 mm Thickness, 150 mm NB,168.3 mm OD & 6.3 mm Thickness, 150 mm NB,168.3 mm OD & 8 mm Thickness, 150 mm NB,168.3 mm OD & 10 mm Thickness, Not Applicable
	Grade Material (as per table 2 of IS 1161)	YSt 210, YSt 240, YSt 310, YSt 355, Not Applicable
	M S Foundation Plate Thickness	10, 12 (millimeter)
	Bearings	Ball Bearing, Tapered Roller Bearing

विवरण/Specification	विशिष्टि का नाम /Specification Name	बिड के लिए आवश्यक अनुमत मूल्य /Bid Requirement (Allowed Values)
	Foot Rest	Fibre Reinforced Plastic, Aluminum casting material, C.I., LDPE, HDPE, Nylon
OTHER REQUIREMENTS	Installation	Included, Not Included
CERTIFICATION	Certification (Safety and Quality Requirements)	As per European Standard EN 16630, No
WARRANTY	Warranty (years)	2, 3, 4, 5 (year)

परेषिती/रिपोर्टिंग अधिकारी तथा मात्रा/Consignees/Reporting Officer and Quantity

क्र.सं./S.No.	परेषिती/रिपोर्टिंग अधिकारी /Consignee Reporting/Officer	पता/Address	मात्रा /Quantity	डिलीवरी के दिन/Delivery Days
1	Parmeshwar Vinayakrao Gomsale	410405,AT MUDHAWARE TQ MAVAL DIST PUNE	1	150

Air Walker / Stroller - Outdoor Gym Equipment (1 pieces)

तकनीकी विशिष्टियाँ /Technical Specifications

[* जेम केटेगरी विशिष्टि के अनुसार / As per GeM Category Specification](#)

विवरण/Specification	विशिष्टि का नाम /Specification Name	बिड के लिए आवश्यक अनुमत मूल्य /Bid Requirement (Allowed Values)
TYPE	Type	Single, Double
CAPACITY	Maximum User Weight (Kg)	100, 110, 120 (kilogram)
MATERIAL	Governing Specification for GI Pipes	BIS specification No IS 1239 (Part 1)- 2004, latest, BIS specification No IS 1161:2014, latest
	All the GI Pipes are ISI marked	Yes, No
	Main Frame	80mm Nominal Bore G.I. Pipe, 100mm Nominal Bore G.I. Pipe, 125 mm Nominal Bore G.I. Pipe, 150mm Nominal Bore G.I. Pipe
	Main Frame Pipe, Class as per IS 1239	Medium, Heavy, Not applicable for pipe as per IS 1161
	leg movement frame	32mm Nominal Bore G.I. Pipe, 40mm Nominal Bore G.I. Pipe, 50mm Nominal Bore G.I. Pipe

विवरण/Specification	विशिष्टि का नाम /Specification Name	बिड के लिए आवश्यक अनुमत मूल्य /Bid Requirement (Allowed Values)
	Leg Movement Frame Pipe, Class as per IS 1239	Medium, Heavy, Not applicable for pipe as per IS 1161
	Handle Frame	25mm Nominal bore G.I. pipe, 32mm Nominal bore G.I. pipe
	Handle Frame Pipe, Class as per IS 1239	Medium, Heavy, Not applicable for pipe as per IS 1161
	Bearings	Ball Bearing, Tapered Roller Bearing
	Foot Rest	Fibre Reinforced Plastic, Aluminum casting material, C.I., LDPE, HDPE, Nylon
	MS Foundation Plate Thickness	10, 12 (millimeter)
	Foundation Pipes with anchoring	750mm deep GI Pipe, supported with M.S. Angle 25 X 25 X 4mm, 500mm deep GI Pipe, supported with M.S. Angle 25 X 25 X 4mm
	Nominal Bore of Foundation Pipe	80mm, 100mm, 125mm, 150mm
	Foundation Pipe, Class as per IS 1239	Medium, Heavy, Not applicable for pipe as per IS 1161
OTHER REQUIREMENTS	Installation	Included, Not Included
CERTIFICATION	Certification (Safety and Quality Requirements)	As per European Standard EN 16630, No
WARRANTY	Warranty (years)	2, 3, 4, 5 (year)

प्रेषिती/रिपोर्टिंग अधिकारी तथा मात्रा/Consignees/Reporting Officer and Quantity

क्र.सं./S.No.	प्रेषिती/रिपोर्टिंग अधिकारी /Consignee Reporting/Officer	पता/Address	मात्रा /Quantity	डिलीवरी के दिन/Delivery Days
1	Parmeshwar Vinayakrao Gomsale	410405,AT MUDHAWARE TQ MAVAL DIST PUNE	1	150

Air Walker / Stroller - Outdoor Gym Equipment (1 pieces)

तकनीकी विशिष्टियाँ /Technical Specifications

[* जेम केटेगरी विशिष्टि के अनुसार / As per GeM Category Specification](#)

विवरण/Specification	विशिष्टि का नाम /Specification Name	बिड के लिए आवश्यक अनुमत मूल्य /Bid Requirement (Allowed Values)
TYPE	Type	Single, Double
CAPACITY	Maximum User Weight (Kg)	100, 110, 120 (kilogram)
MATERIAL	Governing Specification for GI Pipes	BIS specification No IS 1239 (Part 1)- 2004, latest, BIS specification No IS 1161:2014, latest
	All the GI Pipes are ISI marked	Yes, No
	Main Frame	80mm Nominal Bore G.I. Pipe, 100mm Nominal Bore G.I. Pipe, 125 mm Nominal Bore G.I. Pipe, 150mm Nominal Bore G.I. Pipe
	Main Frame Pipe, Class as per IS 1239	Medium, Heavy, Not applicable for pipe as per IS 1161
	leg movement frame	32mm Nominal Bore G.I. Pipe, 40mm Nominal Bore G.I. Pipe, 50mm Nominal Bore G.I. Pipe
	Leg Movement Frame Pipe, Class as per IS 1239	Medium, Heavy, Not applicable for pipe as per IS 1161
	Handle Frame	25mm Nominal bore G.I. pipe, 32mm Nominal bore G.I. pipe
	Handle Frame Pipe, Class as per IS 1239	Medium, Heavy, Not applicable for pipe as per IS 1161
	Bearings	Ball Bearing, Tapered Roller Bearing
	Foot Rest	Fibre Reinforced Plastic, Aluminum casting material, C.I., LDPE, HDPE, Nylon
	MS Foundation Plate Thickness	10, 12 (millimeter)
	Foundation Pipes with anchoring	750mm deep GI Pipe, supported with M.S. Angle 25 X 25 X 4mm, 500mm deep GI Pipe, supported with M.S. Angle 25 X 25 X 4mm
	Nominal Bore of Foundation Pipe	80mm, 100mm, 125mm, 150mm
	Foundation Pipe, Class as per IS 1239	Medium, Heavy, Not applicable for pipe as per IS 1161
OTHER REQUIREMENTS	Installation	Included, Not Included
CERTIFICATION	Certification (Safety and Quality Requirements)	As per European Standard EN 16630, No
WARRANTY	Warranty (years)	2, 3, 4, 5 (year)

परेषिती/रिपोर्टिंग अधिकारी तथा मात्रा/Consignees/Reporting Officer and Quantity

क्र.सं./S.No.	परेषिती/रिपोर्टिंग अधिकारी /Consignee Reporting/Officer	पता/Address	मात्रा /Quantity	डिलीवरी के दिन/Delivery Days
1	Parmeshwar Vinayakrao Gomsale	410405,AT MUDHAWARE TQ MAVAL DIST PUNE	1	150

Parallel Bar - Outdoor Gym Equipment (1 pieces)

तकनीकी विशिष्टियाँ /Technical Specifications

* जेम केटेगरी विशिष्टि के अनुसार / As per GeM Category Specification

विवरण/Specification	विशिष्टि का नाम /Specification Name	बिड के लिए आवश्यक अनुमत मूल्य /Bid Requirement (Allowed Values)
Material	Governing Specification for GI Pipes	BIS specification No IS 1239 (Part 1)- 2004, latest, BIS specification No IS 1161:2014, latest
	All the GI Pipes are ISI marked	Yes, No
	Vertical / Standing Pipes	32 mm Nominal Bore G.I. Pipe, 40 mm Nominal Bore G.I. Pipe, 50 mm Nominal Bore G.I. Pipe, 80 mm Nominal Bore G.I. Pipe, 100 mm Nominal Bore G.I. Pipe, 25mm Nominal Bore G.I. Pipe
	Vertical/ Standing Pipes, Class as per IS 1239	Medium, Heavy, Not applicable for pipe as per IS 1161
	Vertical / StandingPipe (as per Clause 3 of IS 1161) , Nominal Bore & Wall Thickness	80 mm NB with 3.2 mm Thickness, 80 mm NB with 4 mm Thickness, 80 mm NB with 4.8 mm Thickness, 100 mm NB with 3.6 mm Thickness, 100 mm NB with 4.5 mm Thickness, 100 mm NB with 5.4 mm Thickness, 32 mm NB with 2.6 mm Thickness, 32 mm NB with 3.2 mm Thickness, 32 mm NB with 4 mm Thickness, 40 mm NB with 2.9 mm Thickness, 40 mm NB with 3.2 mm Thickness, 40 mm NB with 4 mm Thickness, 50 mm NB with 2.9 mm Thickness, 50 mm NB with 3.6 mm Thickness, 50 mm NB with 4.5 mm Thickness, Not applicable
	Horizontal Pipe	25 mm Nominal Bore G.I. Pipe, 32 mm Nominal Bore G.I. Pipe, 40 mm Nominal Bore G.I. Pipe, 50 mm Nominal Bore G.I. Pipe
	Horizontal Pipe, Class as per IS 1239	Medium, Heavy, Not applicable for pipe as per IS 1161
	Horizontal Pipe (As per Clause 3, of IS 1161) Nominal Bore & Wall Thickness	32 mm NB with 2.6 mm Thickness, 32 mm NB with 3.2 mm Thickness, 32 mm NB with 4 mm Thickness, 40 mm NB with 2.9 mm Thickness, 40 mm NB with 3.2 mm Thickness, 40 mm NB with 4 mm Thickness, 50 mm NB with 2.9 mm Thickness, 50 mm NB with 3.6 mm Thickness, 50 mm NB with 4.5 mm Thickness, 25 mm NB with 2.6 mm Thickness, 25 mm NB with 3.2 mm Thickness, 25 mm NB with 4 mm Thickness, Not applicable
	Grade Material as per table 2 of IS 1161	YSt 210, YSt 240, YSt 310, YSt 355, Not Applicable

विवरण/Specification	विशिष्टि का नाम /Specification Name	बिड के लिए आवश्यक अनुमत मूल्य /Bid Requirement (Allowed Values)
	Foundation Pipes with anchoring	750mm deep GI Pipe, supported with M.S. Angle 25 X 25 X 4mm, 500mm deep GI Pipe, supported with M.S. Angle 25 X 25 X 4mm, 750mm deep GI Pipe, supported with M.S. Angle 25 X 25 X 3 mm, 500mm deep GI Pipe, supported with M.S. Angle 25 X 25 X 3 mm
	Nominal Bore of Foundation Pipe	32 mm, 40 mm, 50 mm, 80 mm, 100 mm, 38 mm
	Foundation Pipe, Class as per IS 1239	Medium, Heavy, Not applicable for pipe as per IS 1161
	Foundation Pipe Pipe (as per IS 1161) as per clause 3, Nominal Wall & Thickness	32 mm NB with 2.6 mm Thickness, 32 mm NB with 3.2 mm Thickness, 32 mm NB with 4 mm Thickness, 40 mm NB with 2.9 mm Thickness, 40 mm NB with 3.2 mm Thickness, 40 mm NB with 4 mm Thickness, 50 mm NB with 2.9 mm Thickness, 50 mm NB with 3.6 mm Thickness, 50 mm NB with 4.5 mm Thickness, 80 mm NB with 3.2 mm Thickness, 80 mm NB with 4 mm Thickness, 80 mm NB with 4.8 mm Thickness, 100 mm NB with 3.6 mm Thickness, 100 mm NB with 4.5 mm Thickness, 100 mm NB with 5.4 mm Thickness, Not Applicable
	M S Foundation Plate Thickness	10, 12 (millimeter)
	Bearings	Ball Bearing, Tapered Roller Bearing, N.A.
	Foot Rest	Fibre Reinforced Plastic, Aluminum casting material, C.I., LDPE, HDPE, Nylon
Other Requirements	Installation	Included, Not Included
Certification	Certification (Safety and Quality Requirements)	As per European Standard EN 16630, No
Warranty	Warranty (years)	2, 3, 4, 5 (year)

परेषिती/रिपोर्टिंग अधिकारी तथा मात्रा/Consignees/Reporting Officer and Quantity

क्र.सं./S.No.	परेषिती/रिपोर्टिंग अधिकारी /Consignee Reporting/Officer	पता/Address	मात्रा /Quantity	डिलीवरी के दिन/Delivery Days
1	Parmeshwar Vinayakrao Gomsale	410405,AT MUDHAWARE TQ MAVAL DIST PUNE	1	150

क्रेता द्वारा जोड़ी गई बिड की विशेष शर्तें/Buyer Added Bid Specific Terms and Conditions

1. **Generic**

OPTION CLAUSE: The Purchaser reserves the right to increase or decrease the quantity to be ordered up to 25 percent of bid quantity at the time of placement of contract. The purchaser also reserves the right to increase the ordered quantity up to 25% of the contracted quantity during the currency of the contract at the contracted rates. The delivery period of quantity shall commence from the last date of original delivery order and in cases where option clause is exercised during the extended delivery period the additional time shall commence from the last date of extended delivery period. The additional delivery time shall be $(\text{Increased quantity} \div \text{Original quantity}) \times \text{Original delivery period (in days)}$, subject to minimum of 30 days. If the original delivery period is less than 30 days, the additional time equals the original delivery period. The Purchaser may extend this calculated delivery duration up to the original delivery period while exercising the option clause. Bidders must comply with these terms.

2. **Scope of Supply**

Scope of supply (Bid price to include all cost components) : Supply Installation Testing and Commissioning of Goods

3. **Turnover**

Bidder Turn Over Criteria: The minimum average annual financial turnover of the bidder during the last three years, ending on 31st March of the previous financial year, should be as indicated in the bid document. Documentary evidence in the form of certified Audited Balance Sheets of relevant periods or a certificate from the Chartered Accountant / Cost Accountant indicating the turnover details for the relevant period shall be uploaded with the bid. In case the date of constitution / incorporation of the bidder is less than 3 year old, the average turnover in respect of the completed financial years after the date of constitution shall be taken into account for this criteria.

4. **Service & Support**

Availability of Service Centres: Bidder/OEM must have a Functional Service Centre in the State of each Consignee's Location in case of carry-in warranty. (Not applicable in case of goods having on-site warranty). If service center is not already there at the time of bidding, successful bidder / OEM shall have to establish one within 30 days of award of contract. Payment shall be released only after submission of documentary evidence of having Functional Service Centre.

5. **Service & Support**

Dedicated /toll Free Telephone No. for Service Support : BIDDER/OEM must have Dedicated/toll Free Telephone No. for Service Support.

6. **Service & Support**

Escalation Matrix For Service Support : Bidder/OEM must provide Escalation Matrix of Telephone Numbers for Service Support.

7. **Certificates**

Bidder's offer is liable to be rejected if they don't upload any of the certificates / documents sought in the Bid document, ATC and Corrigendum if any.

8. **Certificates**

ISO 9001: The bidder or the OEM of the offered products must have ISO 9001 certification.

9. **Certificates**

Material Test Certificate Should Be Sent Along with The Supply. The Material Will Be Checked by Buyer's Lab & the Results of the Lab will be the Sole Criteria for Acceptance of the Item.

10. **Certificates**

The bidder is required to upload, along with the bid, all relevant certificates such as BIS licence, type test

certificate, approval certificates and other certificates as prescribed in the Product Specification given in the bid document.

11. **Buyer Added Bid Specific ATC**

Buyer uploaded ATC document [Click here to view the file.](#)

अस्वीकरण/**Disclaimer**

The additional terms and conditions have been incorporated by the Buyer after approval of the Competent Authority in Buyer Organization, whereby Buyer organization is solely responsible for the impact of these clauses on the bidding process, its outcome, and consequences thereof including any eccentricity / restriction arising in the bidding process due to these ATCs and due to modification of technical specifications and / or terms and conditions governing the bid. If any clause(s) is / are incorporated by the Buyer regarding following, the bid and resultant contracts shall be treated as null and void and such bids may be cancelled by GeM at any stage of bidding process without any notice:-

1. Definition of Class I and Class II suppliers in the bid not in line with the extant Order / Office Memorandum issued by DPIIT in this regard.
2. Seeking EMD submission from bidder(s), including via Additional Terms & Conditions, in contravention to exemption provided to such sellers under GeM GTC.
3. Publishing Custom / BOQ bids for items for which regular GeM categories are available without any Category item bunched with it.
4. Creating BoQ bid for single item.
5. Mentioning specific Brand or Make or Model or Manufacturer or Dealer name.
6. Mandating submission of documents in physical form as a pre-requisite to qualify bidders.
7. Floating / creation of work contracts as Custom Bids in Services.
8. Seeking sample with bid or approval of samples during bid evaluation process. (However, in bids for [attached categories](#), trials are allowed as per approved procurement policy of the buyer nodal Ministries)
9. Mandating foreign / international certifications even in case of existence of Indian Standards without specifying equivalent Indian Certification / standards.
10. Seeking experience from specific organization / department / institute only or from foreign / export experience.
11. Creating bid for items from irrelevant categories.
12. Incorporating any clause against the MSME policy and Preference to Make in India Policy.
13. Reference of conditions published on any external site or reference to external documents/clauses.
14. Asking for any Tender fee / Bid Participation fee / Auction fee in case of Bids / Forward Auction, as the case may be.
15. Buyer added ATC Clauses which are in contravention of clauses defined by buyer in system generated bid template as indicated above in the Bid Details section, EMD Detail, ePBG Detail and MII and MSE Purchase Preference sections of the bid, unless otherwise allowed by GeM GTC.
16. In a category based bid, adding additional items, through buyer added additional scope of work/ additional terms and conditions/or any other document. If buyer needs more items along with the main item, the same must be added through bunching category based items or by bunching custom catalogs or bunching a BoQ with the main category based item, the same must not be done through ATC or Scope of Work.

Further, if any seller has any objection/grievance against these additional clauses or otherwise on any aspect of this bid, they can raise their representation against the same by using the Representation window provided in the bid details field in Seller dashboard after logging in as a seller within 4 days of bid publication on GeM. Buyer is duty bound to reply to all such representations and would not be allowed to open bids if he fails to reply to such representations.

All GeM Sellers / Service Providers are mandated to ensure compliance with all the applicable laws / acts / rules including but not limited to all Labour Laws such as The Minimum Wages Act, 1948, The Payment of Wages Act, 1936, The Payment of Bonus Act, 1965, The Equal Remuneration Act, 1976,

The Payment of Gratuity Act, 1972 etc. Any non-compliance will be treated as breach of contract and Buyer may take suitable actions as per GeM Contract.

[यह बिड सामान्य शर्तों के अंतर्गत भी शासित है /This Bid is also governed by the General Terms and Conditions](#)

जेम की सामान्य शर्तों के खंड 26 के संदर्भ में भारत के साथ भूमि सीमा साझा करने वाले देश के बिडर से खरीद पर प्रतिबंध के संबंध में भारत के साथ भूमि सीमा साझा करने वाले देश का कोई भी बिडर इस निविदा में बिड देने के लिए तभी पात्र होगा जब वह बिड देने वाला सक्षम प्राधिकारी के पास पंजीकृत हो। बिड में भाग लेते समय बिडर को इसका अनुपालन करना होगा और कोई भी गलत घोषणा किए जाने व इसका अनुपालन न करने पर अनुबंध को तत्काल समाप्त करने और कानून के अनुसार आगे की कानूनी कार्रवाई का आधार होगा। In terms of GeM GTC clause 26 regarding Restrictions on procurement from a bidder of a country which shares a land border with India, any bidder from a country which shares a land border with India will be eligible to bid in this tender only if the bidder is registered with the Competent Authority. While participating in bid, Bidder has to undertake compliance of this and any false declaration and non-compliance of this would be a ground for immediate termination of the contract and further legal action in accordance with the laws.

---धन्यवाद/Thank You---